

GRUPPO ELETTROGENO
GENERATING SET
GROUPE ÉLECTROGÈNE



GBH3500MS



Verniciatura per esterni
Marmitta supersilenziata
Olio primo riempimento
Sensore oil alert
Uscita 12 Volt DC
Morsetto di terra
Interruttore protezione 2
Prese schuko



Painting for external use
Exhaust extra silencer
Oil
Oil alert
Outlet 12 Volt DC
Earth connexion
Circuit breaker
2 schuko sockets



Peinture pour extérieur
Echappement ultrasilencieux
Huile
Oil alert
Sortie 12 Volt DC
Borne mise a terre
Disjoncteur thermique
2 Prises schuko

Gruppo elettrogeno - generating set - Groupe électrogène	
Frequenza - Frequency - Fréquence	50 Hz
Potenza monofase - Single-phase power – Puissance monophasé Continua – Cop - Continue	3,1 KVA - 2,5 kW - 230 V - 13,4 A
Potenza monofase - Single-phase power – Puissance monophasé Massima – Stand by - Secours	3,4 KVA – 2,7 kW - 230 V - 14,7 A
Avviamento – Starting - Démarrage	Strappo – Recoil - Corde
Serbatoio – tank - réservoir	3,6 l
Autonomia – Cont .operatine hours – Autonomie	2,5 h
Carburante – Fuel - Carburant	Benzina – gasoline – Essence
Rumorosità residua – Noise - Bruit	DbA 73
Lunghezza x larghezza x altezza - Lenght x width x high – Longueur x largeur x hauteur	590 x 390 x 380 mm
Peso – Weight - Poids	40 kg
Motore OHV a benzina – OHV gasoline engine – Moteur OHV essence	
Tipo - Type	HONDA GX200
Cilindri – cylinders - cylindres	1
Aspirazione - Aspiration	Naturale
Potenza - Power – Puissance 3000 rpm/1' – Hp	4,4
Raffreddamento – Cooling - Refroidissement -	Aria – air - air
Cilindrata - Swept volume - Cylindrée	196 cm ³
Sistema iniezione - Injection system - Systeme injection	TCI
Alternatore- Alternator - Alternateur	
Autoeccitato ed autoregolato - Self-excited and self-regulated - Auto-excités - autorégulés	
Poli - Poles	2
Distorsione armonica - - Harmonic distortion - Distorsion harmonique	< 5%
Grado di protezione - Protection degree – Degré de protection	IP 23