

**GRUPPO ELETTROGENO  
GENERATING SET  
GROUPE ELECTROGENE**



## GBH7000MS



**Verniciatura per esterni  
Marmitta supersilenziata  
Olio primo riempimento  
Sensore oil alert  
Interruttore differenziale  
Morsetto di terra  
Contaore  
2 Prese CEE**



**Painting for external use  
Exhaust extra silencer  
Oil  
Oil alert  
Differential circuit breaker  
Earth connexion  
Hourmeter  
2 CEE sockets**



**Peinture pour extérieur  
Echappement ultrasilencieux  
Huile  
Oil alert  
Disjoncteur différentiel  
Borne mise a terre  
Compteur horaire  
2 Prises CEE**

Gruppo elettrogeno - Generating set - Groupe électrogène	
Frequenza - Frequency - Fréquence	50 Hz
Potenza monofase - Single-phase power – Puissance monophasé Continua – Cop - Continue	Kva 6,5 – Kw 5,2 – V230 – A 28
Potenza monofase - Single-phase power – Puissance monophasé Massima – Stand by - Secours	Kva 7,2 – Kw 5,7 – V230 – A 31
Avviamento – Starting - Démarrage	Strappo – Recoil - Corde
Serbatoio – tank - réservoir	6,5 l
Autonomia – Cont .operating hours – Autonomie 75%	2,5 h
Carburante – Fuel - Carburant	Benzina – gasoline – Essence
Rumorosità residua – Noise - Bruit	DbA 72
Lunghezza x larghezza x altezza - Lenght x width x high – Longueur x largeur x hauteur	780 x 520 x 560 mm
Peso – Weight - Poids	73 kg
Motore OHV a benzina – OHV gasoline engine – Moteur OHV essence	
Tipo - Type	<b>HONDA GX390</b>
Cilindri – cylinders - cylindres	1
Aspirazione - Aspiration	Naturale
Potenza - Power – Puissance 3000 rpm/1' – Hp	13
Raffreddamento – Cooling - Refroidissement -	Aria – air - air
Cilindrata - Swept volume - Cylindrée	389 cm <sup>3</sup>
Sistema iniezione - Injection system - Systeme injection	TCI
Alternatore- Alternator - Alternateur	
Autoeccitato ed autoregolato - Self-excited and self-regulated - Auto-excités - autorégulés	
Poli - Poles	2
Distorsione armonica - - Harmonic distortion - Distorsion harmonique	< 5%
Grado di protezione - Protection degree – Degré de protection	IP 23