

GRUPPO ELETTOGENO
GENERATING SET
GROUPE ELECTROGENE



GDL4000MS



Telaio tubolare
Verniciatura per esterni
Marmitta
Liquidi di primo
riempimento
Interruttore magnetotermico



Tubular frame
Painting for external use
Exhaust muffler
Oil
Magnetothermal circuit
breaker



Cadre tubulaire
Peinture pour extérieur
Echappement
Huile
Disjoncteur magnétothermique

Gruppo elettrogeno - Generating set - Groupe électrogène	
Frequenza - Frequency - Fréquence	50 Hz
Potenza monofase - Single-phase power – Puissance monophasé Continua – Prime - Continu	Kva 4,2 – Kw 3,3 – V230 – A 18,2
Potenza monofase - Single-phase power – Puissance monophasé Massima – Stand by - Secours	Kva 4,6 – Kw 3,6 – V230 – A 20
Avviamento – Starting - Démarrage	Corda con autoavvolgente-recoil-corde avec lanceur
Serbatoio – tank - réservoir	4,3 l
Autonomia – Working hours – Autonomie 75%	3,5 h
Rumorosità residua – Noise - Bruit	78 dB(A) 7m
Lunghezza x larghezza x altezza - Length x width x high – Longueur x largeur x hauteur	780 x 520 x 560 mm
Peso – Weight - Poids	75 kg
Motore Diesel - Diesel engine – Moteur Diesel	
Tipo - Type	KOHLER/LOMBARDINI 15 LD 350
Cilindri – cylinders - cylindres	1
Aspirazione - Aspiration	Aspirato – Natural - Naturelle
Potenza - Power – Puissance 3000 rpm/1' – Kw – Cv	4,3 – 5,8
Raffreddamento – Cooling - Refroidissement -	Aria - Air
Cilindrata - Swept volume - Cylindrée	cm ³ 349
Sistema iniezione - Injection system - Systeme injection	Diretta – Direct - Directe
Consumo combustibile - Fuel consumption - Consommation combustible 75%	1,2 l/h
Alternatore- Alternator - Alternateur	
Monosupporto autoeccitato ed autoregolato - Single bearing self-excited and self-regulated - Mono-palier auto-excités - autorégulés	
Poli - Poles	2
Distorsione armonica - - Harmonic distortion - Distorsion harmonique	< 5%
Grado di protezione - Protection degree – Degré de protection	IP 23
Collegamenti degli avvolgimenti –Winding connection - Connexion des bobinages	Stella + neutro – Star + neutral Etoile+neutre